

SPECIAL PROVISIONS

TRACTORS

16. Wheel Type Tractor. All lugs, cleats, flanges or projections shall be removed or road bands installed before operating on any pavement or gravel surface.
 17. Track Layer Type Tractor. If the tread of the track has projects or corrugations, a filler block shall be placed on each section so that a flat bearing surface will be in contact with the pavement.
 18. Pilot Wheel. If equipped with a pilot wheel, the ring of the same shall be removed, covered or supplemented by additional rings such that the width of the bearing surface shall be not less than five inches.
 19. Weight per Inch Width. The blocks, road bands or rings shall be of sufficient width to furnish a flat bearing, such that the weight per inch of tread shall not exceed five hundred (500) pounds.
 20. Crossing Traveled Way. If the equipment is simply to cross from one side of the road to the other, the pavement and shoulders may be covered with planks at least 2 inches thick, or by use of heavy bolting of sufficient width, and the equipment permitted to pass thereover without the placing of filler blocks or road bands. This precaution may be omitted if the Permittee deposits a Surety Bond in the amount of \$100 to reimburse the County for any damage to the road surface caused by such crossings. Permit is not required for farm tractors with plane tread or equipped with filler blocks.
 21. Trailers. Not more than two trailers shall be moved over the highway at any one time behind the equipment.
 22. Projections on Trailer Trade. Any projections on the tread of trailers shall be removed or protected as for tractors.
 23. Towing Farm Implements. When farm implements are being towed, the paragraph above shall govern where they apply.
 24. Turning Tractor. In turning on or off the highway special care shall be taken to so handle the equipment that the edges of the pavement will not be broken, and the shoulders will not be cut up.
 25. Use Care In Trailing Plows, etc. In trailing plows, discs, and similar equipment, shall be used so that the implements do not cut or damage the road surface.
- WEIGHT AND SIZE OF LOADS
26. Limit of Load. The weight or size of load shall be within the limit stated on the face of this permit.
 27. Maximum Weight and Size. The maximum limits for weight and the size of the vehicles and loads set forth in the vehicle code shall not be exceeded except as specifically stated on the face of this permit.
 28. Kind of Equipment. Buildings are to be moved with regular house moving equipment.
 29. Interference With Traffic. The moving shall be done at the time of day and in a manner which will cause the least interference with traffic.
 30. Cleaning Up Right of Way. Upon completion of the moving work, all timbers and equipment shall be removed and the Right of Way left in the same condition as before the work started.
 31. Do Not Disturb Roadway Surface. No wedge, bar or spike shall be driven in the surface of the County highway.
 32. Care of Trees. No trees shall be cut, trimmed used for attaching cable or in any way disturbed.
 33. Care of Overhead Wires. Permittees must notify the owner of all overhead lines subject to disturbance or damage by his operations at least twenty-four hours in advance of such work and mutually agreeable arrangements shall be made between the parties affected. (This provision does not authorize owners of overhead lines to limit work allowed under this permit).